

ALD15VTII D Series

modern style user friendly durable

acode®

touchscreen monitor

15" + 7" 8.4" 10.4"
2nd LCD display flat screen



Display Size	15"
Optimal Resolution	1024 x 768
Brightness	140 cd/m ² (typ)
Contrast Ratio	600:1
Response Time	8 ms (typ)
Degree	160 degree (H) / 160 degree (V)
Input Video Signal	D-Sub 15 pins/ DVI-D
Touch Function	USB or RS232
Power Consumption	20W Operation 3W Standby
Input Frequency	Horizontal : 31.5~60.2 kHz Vertical : 56.3~75 kHz
Power Supply	DC 12V +/- 10%
Temperature	Operation: 0 ~ 40 degree C Storage: -10 ~ 50 degree C
Humidity	Operation: 20% ~ 80% Storage: 10% ~ 90%
Weight	4.67Kgs (10.3Lbs)
Physical Dimension	365.2 x 338.6 x 200 (mm)



7"

Display Size	7"
Optimal Resolution	800 * 480
Brightness	350 cd/m ² (typ)
Contrast Ratio	500:1 (typ)
Response Time	25 ms (typ)
Viewing Angle (L/R/U/D)	70 / 70 / 50 / 70
Input Video Signal	USB B Type
Power Consumption	2.5W
Input Frequency	Horizontal: 31.5~60.2KHz Vertical: 56.3Hz~75Hz
Power Supply	DC 5V +/- 10%
Temperature	Operating: 0~40 degree C Storage: -10~50 degree C
Humidity	Operating: 20% ~ 80% Storage: 10% ~ 90%
Weight	0.5 Kgs (1.27 Lbs)
Physical Dimension	184.5 x 118 x 34.5 (mm)



8.4"

Display Size	8.4"
Optimal Resolution	800 * 600
Brightness	180 cd/m ² (typ)
Contrast Ratio	600:1 (typ)
Response Time	8 ms (typ)
Viewing Angle (L/R/U/D)	75 / 75 / 50 / 60
Input Video Signal	USB B Type
Power Consumption	2.5W
Input Frequency	Horizontal: 31.5~60.2KHz Vertical: 56.3Hz~75Hz
Power Supply	DC 5V +/- 10%
Temperature	Operating: 0~40 degree C Storage: -10~50 degree C
Humidity	Operating: 20% ~ 80% Storage: 10% ~ 90%
Weight	680g Net
Physical Dimension	199.7 x 165 x 33.7 (mm)



10.4"

Display Size	10.4"
Optimal Resolution	800 * 600
Brightness	250 cd/m ² (typ)
Contrast Ratio	500:1 (typ)
Response Time	20 ms (typ)
Viewing Angle (L/R/U/D)	70 / 70 / 50 / 70
Input Video Signal	USB B Type
Power Consumption	2.5W
Input Frequency	Horizontal: 31.5~60.2KHz Vertical: 56.3Hz~75Hz
Power Supply	DC 5V +/- 10%
Temperature	Operating: 0~40 degree C Storage: -10~50 degree C
Humidity	Operating: 20% ~ 80% Storage: 10% ~ 90%
Weight	0.8 Kgs
Physical Dimension	224 x 197.4 x 36.4 (mm)