

ALD15VTII Series

acode®

rugged design resistive touch design for high traffic POS environment

15" touchscreen monitor taiwan touch



Display Size	15"
Optimal Resolution	1024 x 768
Brightness	140 cd/m ² (typ)
Contrast Ratio	600:1
Response Time	8 ms (typ)
Degree	160 degree (H) / 160 degree (V)
Input Video Signal	D-Sub 15 pins/ DVI-D
Touch Function	USB or RS232
Power Consumption	20W Operation 3W Standby
Input Frequency	Horizontal : 31.5~60.2 kHz Vertical : 56.3~75 kHz
Power Supply	DC 12V +/- 10%
Temperature	Operation: 0 ~ 40 degree C Storage: -10 ~ 50 degree C
Humidity	Operation: 20% ~ 80% Storage: 10% ~ 90%
Weight	4.67Kgs (10.3Lbs)
Physical Dimension	365.2 x 338.6 x 200 (mm)

Unlike All-in-One POS terminal that is composed of hardware peripherals supplied from a single manufacturer, purchase hardware individually provides total flexibility in choosing hardware components and convenient replacement and repair.

Create Your Own Hardware Package

Options:



+ mount a compact computer



+ mount a 2nd LCD display flat screen
7" 8.4" 10.4"



+ use with a LCD customer pole display flat screen
7" 8.4" 10.4"