

# ALD07U/V 7-Inch LCD Graphic Display



	<b>ALD07U USB to VGA</b>	<b>ALD07V VGA</b>
Display Size	7"	7"
Active Area	153.6 x 86.64 mm	153.6 x 86.64 mm
Optimal Resolution	800 x 480	800 x 480
Brightness	200 nits (typ)	200 nits (typ)
Contrast Ratio	500:1 (typ)	500:1 (typ)
Response Time	25 ms (typ)	25 ms (typ)
LCD Viewing Angle(L/R/U/D)	70 / 70 / 50 / 60	70 / 70 / 50 / 60
Tilt Angle	35° (V) / 70° (H) / with pole	35° (V) / 70° (H) / with pole
Input Video Signal Connector	USB to VGA	D-Sub 15 pins
Input Frequency	Horizontal: 31.5-60.2 kHz Vertical : 56.3Hz-75Hz	Horizontal: 31.5-60.2 kHz Vertical : 56.3Hz-75Hz
Power Consumption	2.5W	6W
Power Supply	NONE (Power from USB)	DC 12V 1.5A +/- 10%
Temperature	Operating : 0°C~40°C Storage : -10°C~50°C	Operating : 0°C~40°C Storage : -10°C~50°C
Humidity	Operating : 20%~80% Storage : 10%~90%	Operating : 20%~80% Storage : 10%~90%
Weight	500g (Net)	500 g (Net)
Dimensions	192 x 115 x 34.5 mm	192 x 115 x 34.5 mm
Approvals	CE / FCC / BSMI / CCC	CE / FCC / BSMI / CCC
Wall Mount (Screw Holes)	VESA 75 x 75 mm	VESA 75 x 75 mm
Stand Base (Options)	3" Base Only or 7" Pole + Base	3" Base Only or 7" Pole + Base

All specifications are subject to change without prior notice.